

<u>CROSS SECTION</u> See sheets 10 & 11 for Superstructure.

full width of bridge.

SECTION AT ABUTMENTS

@ Rt. L's


DESIGNED - A.S.L.

DRAWN - D.A.B.

CHECKED - S.W.M.

1" Fabric Brg. Pad 1"  $\phi$  x 2'-6" Dowel Rods

After beams are in place drill 12' \( \phi\) holes in cap & grout dowel rods in place.
Rods to be grouted and allowed to cure (Min. 24 Hrs.) prior to grouting shear keys.



3<sup>3</sup>4'' (Typ.)

1<sup>3</sup>4''
(Typ.)

DETAIL A

		D RENWICK, INC INEERS - LAND SURVEYO
HER	SPRINGFIELD,	ON DRIVE, SUITE 2 LLINOIS 62703 w.hlrengineering.co
184,000959	ECOLONIAL DECLON EIDA	LS / PE / SE CORPORATION

T.R.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.	
272	08-02136-00-BR	FRANKLIN	16	12	
BENTO	N ROAD DISTRICT	CONTRACT NO. 99426			
FED. RO	OAD DIST. NO.   ILLINOIS FED. AI	D PROJECT BROS	-0055(061)		