



Notes: Load carrying components designated "NTR" shall conform to the Impact Testing Requirement, Zone 2.
 All diaphragms shall be installed as steel is erected and secured with erection pins and bolts except otherwise noted. Individual diaphragms at supports may be temporarily disconnected to install bearing anchor rods.
 All structural steel plates including flange plates, web plates and bearing stiffener plates shall be AASHTO M 270, Grade 50.

DESIGNED - Dewey H. Couitas	EXAMINED - <i>Joanne F. [Signature]</i>	DATE - OCTOBER 9, 2014	STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION	STRUCTURAL STEEL STRUCTURE NO. 032-0124	F.A.U. R.T.E. - 5966	SECTION - (32-2) HBR-6	COUNTY - GRUNDY	TOTAL SHEETS - 98	SHEET NO. - 63	
CHECKED - Frank W. Sharpe	PASSED - <i>Carl [Signature]</i>	REVISED			CONTRACT NO. 66B27					
DRAWN - h.t. duong	ACTING ENGINEER OF BRIDGES AND STRUCTURES	REVISED			SHEET NO. 16 OF 24 SHEETS					
CHECKED - DHC/FWS					ILLINOIS FED. AID PROJECT					