

CHICAGO, ILLINOIS

PLOT DATE = 7/30/2014

DATE 05 03 2013

REVISED

SHEET NO. S5 OF S2

NOTES

1. Detail I - With Bar Splicer or Couplers: Connect one (1) 1'' x 7' 'x ''W'' steel ft to the top layer of couplers with $2 - \frac{5}{8}$ " ϕ bolts screwed to coupler at approximate Q of each barrier panel, 2. Detail II - With Extended Reinforcement Bars: Connect one (1) 1" x 7" x "W" steel P to the concrete slab or concrete wearing surface with $2 - \frac{5}{8}$ " ϕ Expansion Anchors or cast in place inserts spaced between the top layer of reinforcement at approximate \mathcal{Q} of each barrier panel.

3. Cost of anchorage is included with Temporary Concrete Barrier. 4. The 1" x 7" x "W" plate shall not be removed until stage II construction forms and all reinforcement bars are in place and the concrete is ready to be placed.



FOR STAGE CONSTRUCTION	F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
0. 048–0091	74	48-[(25B)BR, BR-1]	KNOX	131	51
	CONTRACT NO. 68B85				
S25 SHEETS	ILLINOIS FED. AID PROJECT				