F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS		
80/94	2626.2-R-2	COOK/LAKE	1207	301	
STA. TO STA.					
FED. ROA	D DIST. NO.	ILLINOIS FED. AID PROJECT			
CONTRAC	CONTRACT NO. 62114 INDOT DES. NO. 0100987				

## **GENERAL NOTES**

- Standard Drawing 715-BKFL-01, 03, 05 and 07 illustrate the requirements for pipe installations utilizing structure backfill. Standard Drawings 715-BKFL-02, 04, 06, and 08 illustrate the requirements for pipe installations using flowable backfill.
- Protective cover shall be constructed prior to running heavy equipment over installed pipes. The minimum covers are listed below:
  - a.) 0.5 m for Bc < 450, where Bc = pipe diameter or span
  - b.) 0.9 m for 450 < Bc ≤ 1350
  - c.) 1.2 m for Bc > 1350
- (3) For backfill purposes, paved shoulders, curbs, and sidewalks are considered pevernent.
- Method 1 backfill shall be utilized for all Type 2 or 5 pipe installed parallel to the maintine or public road approaches and within 1525 of pavement. Method 2 backfill shall be utilized for such pipe installed outside 1525 from pavement.
- If the existing ground line is less than Vc above the proposed top of pipe elevation, the embankment shall be constructed to at least Vc above the proposed top of pipe elevation prior to pipe installation. Vc = 300 for Bc ≤ 450 and Vc = 500 for Bc > 450.
- in paved median areas, structure backfill shall be utilized instead of compacted earth backfill between the Vc dimension above the pipe and the top of the trench.
- 7 Flowable or structure backfill shall be encased by compacted earth backfill. The minimum encasement shall be 0.6 m. If necessary, the 2:1 slope between the between the flowable or structure backfill and the encasement shall be modified to maintain the minimum 0.6 m encasement.
- Flowable backfill shall be utilized for plastic pipes fabricated of non hydrostatic design basis rated resins and installed at locations where method 1 backfill is required.

All Dimension are in mm unless otherwise specified

INDIANA DEPARTMENT OF TRANSPORTATION

PIPE STRUCTURE BACKFILL

MARCH 2005

STANDARD DRAWING NO. 715-BKFL-09

NO. 9750 STATE OF

/s/ Richard L. VonCleave 3-01-05 DESIGN STANDARDS ENGINEER DATE

/s/ Alchord K.Smutzer 3-Di-Di CHEF HICH MAY ENGINEER DATE