GENERAL NOTES

À

Reinforcement bars shall conform to the requirements of AASHTO M 31M or M322M Grade 400.

2. The Contractor shall drive 4 test piles in permanent locations spaced approximately 60 m apart, as directed by the Engineer before ordering the remainder of the piles.

3. All dimensions are in millimeters (mm) except as noted.

4. All construction joints shall be bonded.

INDEX OF SHEETS

SHEET NO.	TITLE
S-1	General Plan
5-2	Index of Sheets. General Nates and Total Bill of Material
5-3	Plan and Elevation (1 of 7)
5-4	Plan and Elevation (2 of 7)
S-5	Plan and Elevation (3 of 7)
S-6	Plan and Elevation (4 of 7)
S-7	Plan and Elevation (5 of 7)
S-8	Plan and Elevation (6 of 7)
5-9	Plan and Elevation (7 of 7)
S-10	Wall Sections and Details (1 of 2)
S-11	Wall Sections and Details (2 of 2)
5-12	Rustication Finish Details
S-13	Concrete Pile Details
S-14	Boring Logs (1 of 6)
S-15	Boring Logs (2 of 6)
S-16	Boring Logs (3 of 6)

Boring Logs (4 of 6) Boring Logs (5 of 6) Boring Logs (6 of 6)

S-17 S-18 S-19



TYPICAL SECTION

DESIGNED	KFA
CHECKED	BPS
DRAWN	MJB
CHECKED	GSP

ROUTE NO.	SECTION	COLNITY		TOTAL SHEETS	SHEET NO.	SHEET NO. 5-2
F. A. I. 80/94	2628.2-R-2	LAKE COUNTY, INDIANA		1207	899	19 SHEETS
	*****	ILLINDIS	FEG. ALD PR	OJECT-		
CONTRAC	T NO.	62114	IND	OT DES.	. NO. O	100987

TOTAL BILL OF MATERIAL

ITEM	UNIT	QUANTITY
Test Pile, 356 mm	Each	4
Excavation, Foundation, Unclassified	m 3	2,475.5
Concrete, A, Substructure	т ³	791.6
Rustication Finish	m²	559
Reinforcing Bars, Epoxy Coated	kg	53,100
Surface Seal	L Sum	0.02
Pile, Concrete, Steel Shell Encased, 6.35 mm, 356 mm	m	2,670.0
Geocomposite Wall Drain	т ²	529
Pipe, Underdrain, Perf., 1.63 mm, 150 mm	т	151.0
Noise Abatement Wall Anchor Rod Assembly	Each	40
B Borrow	m ³	276.3
Structural Backfill	т ³	1,762.3
Masonry Coating	L Sum	0.04

(IN) Indiana Pay Items, denoted by "(Indiana)" in Special Provisions and Summary of Quantities.

