






SECTION A-A *


★ DIMENSIONS OF THE CURB & GUTTER AT SECTION A-A ARE SHOWN ON STATE STANDARD 606001. FOR DETAILS OF OUTLET FOR CONCRETE CURB & GUTTER, TYPE B-6.24 (B-15.60) SEE STATE STANDARD 606006.





SECTION D-D





SECTION C-C

SCALE: NONE

SECTION B-B

GENERAL NOTES

- GUTTER OUTLET SHALL BE TIED TO THE PAVEMENT IN ACCORDANCE WITH DETAILS FOR LONGITUDINAL CONSTRUCTION JOINT SHOWN ON STANDARD 420001.
- 2. TIE BARS SHALL BE NO. 20 (NO.6) AT 24" (600) CENTERS UNLESS OTHERWISE SHOWN.
- 3. IF THE AVERAGE GRADE OF PAVEMENT FOR THE DISTANCE FROM SECTION A-A TO D-D EXCEEDS 2%, THIS DISTANCE SHALL BE INCREASED 6' (1.8 m) FOR EACH 1% INCREASE IN GRADE.

METHOD OF MEASUREMENT

FOR SECTION A-A TO E-E AND CURTAIN WALL=

1.25 CU. YDS. (0.96³m) CLASS SI CONCRETE (OUTLET) FOR 9" (225) PAV'T.
1.27 CU. YDS. (0.96³m) CLASS SI CONCRETE (OUTLET) FOR 10" (250) PAV'T.

FOR SECTION F-F= 0.045 CU. YDS. $(0.03^3$ m) CLASS SI CONCRETE PER ft. (m).


ALL DIMENSIONS ARE IN INCHES (MILLIMETERS) UNLESS OTHERWISE SHOWN.



STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

OUTLET FOR CONCRETE CURB AND GUTTER						F.A. RTE	SECTION			COUNTY	TOTAL SHEETS	SHEE NO.
						BD600-01 (B		(BD-03	3)	CONTRACT NO		
	SHEET 1	OF 1	SHEETS	STA	TO STA			ILLINOIS	EED A	ID PROJECT		

SECTION E-E



SECTION F-F

SECTION G-G