

GENERAL NOTES IN USE

DOC NAME

COMMENTS

[100A](#)

DISCUSS USE OF THIS GENERAL NOTE WITH PROJECT ENGINEER.

[100B](#)

USE ONLY WHEN THERE IS A SIGNIFICANT AMOUNT OF EARTHWORK, WIDENING, OR DITCH GRADING. DISCUSS THE USE OF THIS GN WITH PROJECT ENGINEER.

[105.09A](#)

EFFECTIVE JULY 1, 1999 ALL VERTICAL CONTROL SURVEYS BEING DONE BY OR FOR THE DEPARTMENT OF TRANSPORTATION SHOULD USE THE NAVD 88 AS THE DATUM OF REFERENCE FOR ALL ELEVATIONS. IF ANY QUESTIONS, CONTACT SURVEYS UNIT.

[107.12](#)

USE WHEN WORK ENCROACHES ON RAILROAD RIGHT-OF-WAY. SECURE THE CONTACT INFORMATION FROM THE PROJECT SUPPORT UNIT.

[201](#)

USE THIS GENERAL NOTE WHEN THE PLANS INCLUDE TREE REMOVAL BY UNITS DIAMETER OR ACRES.

[205](#)

USE WHEN WIDENING EXISTING EMBANKMENTS. GET BENCHING DIMENSIONS FROM THE GEOTECHNICAL ENGINEER IN MATERIALS.

[403](#)

USE THIS GENERAL NOTE FOR CONVENTIONAL A-1, A-2 OR A-3 SEAL COAT WORK. DISCUSS DETAILS WITH MATERIALS DURING DESIGN.

[403A](#)

THIS GENERAL NOTE IS FOR SHOULDER SEAL COAT WORK. DISCUSS DETAILS AND CHOICE OF AGGREGATE WITH MATERIALS DURING DESIGN.

GENERAL NOTES IN USE

DOC NAME

COMMENTS

[406H](#)

DISCUSS THE USE OF THIS GENERAL NOTE WITH MATERIALS.

[406M](#)

USE ON RESURFACING CONTRACTS THAT HAVE STRUCTURES WITHIN THE LIMITS OF THE PROJECT

[406S](#)

USE ON ALL RESURFACING CONTRACTS. SEE DESIGNERS NOTE

[408B](#)

ASSURES COMPACTION REQUIREMENT FOR INCIDENTAL HOT-MIX ASPHALT SURFACING AT SPECIFIC CRITICAL LOCATIONS. DISCUSS LOCATIONS WITH MATERIALS (MAJOR SIDESTREETS, ETC.) AND SHOW THE LOCATIONS IN THE GENERAL NOTE.

[440B](#)

USE WHEN PLACING NEW PCC WORK WHERE EXISTING CURB AND GUTTER, OR OTHER PCC ITEMS ARE TO BE REMOVED.

[440L](#)

USE WHEN HMA BEING MILLED CONTAINS STEEL SLAG COARSE AGGREGATE.

[501A](#)

USE ON JOBS WHERE THE CONTRACTOR WILL REMOVE, OR OTHERWISE WORK ON THE EXISTING STRUCTURAL STEEL. CONSULT WITH BRIDGE AND HYDRAULICS SECTION REGARDING HISTORY OF THE PARTICULAR STRUCTURE AND PRESENCE OF LEAD.

[506](#)

THIS IS THE DISTRICT'S STANDARD COLOR SCHEME FOR PAINTING STEEL BEAMS. USE THIS UNLESS A NEED FOR A SPECIAL COLOR SCHEME IS KNOWN.

GENERAL NOTES IN USE

DOC NAME

COMMENTS

[542.07](#)

USE IF THE CAST-IN-PLACE END TREATMENTS ARE NOT SUITABLE. USUALLY PRECAST FLARED END SECTIONS ARE PREFERRABLE WITHIN THE CLEAR ZONE.

[542B](#)

GIVES DESIGN ASSUMPTION FOR ENTRANCE CULVERTS. MAKE SURE THAT YOU USE THIS ONLY IF IT MATCHES YOUR DESIGN.

[551](#)

CONFIRM WITH OPERATIONS THAT THEY DO NOT WISH TO SALVAGE THE STORM SEWERS BEFORE INCLUDING THIS GENERAL NOTE.

[601](#)

USE ON NEW UNDERDRAIN INSTALLATIONS OR REPLACEMENTS WHERE THE PLUG WILL RECEIVE ADDITIONAL OVERLAY. DO NOT USE THE POROUS PLUG FOR THE FINAL SURFACE OVER UNDERDRAINS.

[601A](#)

USE ON PROJECTS THAT HAVE PIPE DRAINS

[663A](#)

USE TO CONTROL DUST WHEN TRAFFIC WILL RUN ON AGGREGATE BASES. GIVES APPLICATION RATE FOR THE JOB.

[703A](#)

USE ON ALL JOBS WHICH WILL OBLITERATE THE EXISTING MARKINGS DURING CONSTRUCTION.

[781](#)

STANDARD GENERAL NOTE FOR RAISED REFLECTIVE PAVEMENT MARKERS.