

ELEVATION

DIMENSIONS


Location	A	В	С	D	E	F

BILL OF MATERIAL

Bar	No.	Size	Length	Shape		
h(E)	7	#5	_'_"			
n(E)		#5	'_ "			
s(E)		#5	<u>'_</u> "			
	_					
Reinforcement Bars, Epoxy Coated			Pound	000		
Concrete			Cu. Yd.	00.0		
Structures			0u. ru.	00.0		

* n(E)h(E)

SECTION A-A



*Epoxy grout n(E) bars in 9" min. holes according to Article 584 of the Standard Specifications.

Plan dimensions and details relative to existing plans are subject to nominal construction variations. The Contactor shall field verify existing dimensions and details affecting new construction and make necessary approved adjustments prior to construction or ordering of materials. Such variations shall not be cause for additional compensation for a change in scope of the work, however, the Contractor will be paid for the quantity actually furnished at the unit price bid for the work.

Reinforcement bars designated (E) shall be epoxy coated.

Revised per Structural Services Manual Section 2.7.7 Crashwall Extensions

Two Column Trapezoidal Pier Shown. (Multiple Columns Similar)

					ennier)		DIS	TRICT 5 DETAI	L NO. XX002909B	
PLC	USER NAME = Bridgette.Pierson	DESIGNED - KJT	REVISED - KJT 5/2011				F.A.	SECTION	COUNTY TOTAL SHEET	
		DRAWN -	REVISED - SWN 3/6/2017	STATE OF ILLINOIS CRASHWALL		IWALL EXTENSION (TRAPEZOIDAL COLUMN PIER)				
	PLOT SCALE = 0.16666633 '/ In.	CHECKED -	REVISED - TJB 6/7/2022	DEPARTMENT OF TRANSPORTATION				CONTRACT NO.		
	PLOT DATE = 7/18/2024	DATE - 11/2006	REVISED - TJB 7/17/2024		SCALE:	SHEET 1 OF 1 SHEETS STA. TO STA.		ILLINOIS FED. AID PROJECT		



GENERAL NOTES

Reinforcement bars shall conform to the requirements of AASHTO M-31, M-42 or M-53 Grade 60.

The cost of epoxy grouting bars shall be included with reinforcement bars (epoxy coated).