

MULTI-LANE/DIVIDED

GENERAL NOTES

3 e 40' (12 m) O.C.

- 1. MARKERS IJSED WITH DASHED LINES SHALL BE CENTERED IN THE GAP BETWEEN SEGMENTS.
- 2. MARKERS JSED ADJACENT TO SOLID LINES SHALL BE OFFSET 2 TO 3 (EO TO 75) TOWARD TRAFFIC AS SHOWN.
- 3. MARKERS THROUGH TANGENTS LESS THAN 500' (150 m) IN LENGTH BITWEEN CURVES SHALL BE INSTALLED AT THE LESSER CF THE TWO CURVE SPACINGS.

LANE MARKER NOTES

- A. USE DOUBLE LANE LINE MARKERS SPACED AS SHOWN.
- B. REDUCE TO 40' (12 m) O.C. ON CURVES WHERE ADVISORY SPEEDS ARE 10 M.P.H (2' km/h) LOWER THAN POSTED SPEEDS.

SYMBOLS

---- YELLOW STRIPE

80' (24 m) O.C. SEE NOTE B

40' (12 m) O.C.

1 5

SEE NOTE A-


TWO-WAY LEFT TURN

- ONE-WAY AMBER MARKER
- TWO-WAY AMRER MARKER

ONE-WAY CRYSTAL MARKER (W/O)

DESIGN NOTES

- 1. DOUBLE LANE LINE MARKERS SHALL BE USED UNLESS SPECIFIED OTHERWISE.
- 2. EXCEPT AS SHOWN ON THE LANE REDUCTION TRANSITION AND FREEWAY EXIT RAMP DETAIL, MARKERS ARE NOT TO BE SPECIFIED ON RIGHT EDGE
- 3. THE EXACT MARKER LIMITS, SPACING, AND COLOR SHOULD BE INCLUDED IN THE PLANS.
- MARKERS SHOULD NOT BE USED ALONGSIDE CURBS EXCEPT FOR EXTREMELY SHORT SECTIONS OF CURBS WHERE NOT MORE THAN TWO MARKERS WOULD BE INVOLVED.



LEFT TURN

All dimensions are in inches (millimeters) unless otherwise shown.

FILE NAME =	USER NAME = abreuah	DESIGNED -	REVISED - T. RAMMACHER 09-19-94			F.A.I. SECTION COUNTY TOTAL SHEET NO.
ci\pw.work\PWIDOT\ABREUAH\dØ166688\Dist	td.dgn	DRAWN -	REVISED -T. RAMMACHER 03-12-99	STATE OF ILLINOIS	TYPICAL APPLICATIONS	
	PLOT SCALE = 100.0000 '/ IN.	CHECKED -	REVISED -T. RAMMACHER 01-06-00	DEPARTMENT OF TRANSPORTATION	RAISED REFLECTIVE PAVEMENT MARKERS (SNOW-PLOW RESISTANT)	290 (531-3.1, 0305-302 K) RS-5 COOK 314 (303)
	PLOT DATE = 1/23/2010	DATE -	REVISED - C. JUCIUS 09-09-09		SCALE: NONE SHEET NO. 1 OF 1 SHEETS STA. TO STA.	FED, ROAD DIST, NO. 1 THE INDISTRED AND PROFEST