INDEX OF SHEETS

SHEET

DESCRIPTION

- 1 COVER SHEET
- 2 INDEX, GENERAL NOTES AND HIGHWAY STANDARDS
- 3 SUMMARY OF QUANTITIES
- 4 TYPICAL SECTIONS
- 5 NOT USED
- 6-11 ROADWAY AND PAVEMENT MARKING PLANS
- 12-20 DETECTOR LOOP REPLACEMENT
- 21 PAVEMENT PATCHING FOR HMA SURFACED PAVEMENT (BD22)
- 22 BUTT JOINTS AND BITUMINOUS TAPER (BD32)
- 23 TRAFFIC CONTROL AND PROTECTION FOR SIDEROADS, INTERSECTIONS AND DRIVEWAYS (TC10)
- 24 RAISED REFLECTIVE PAVEMENT MARKERS (SNOW PLOW RESISTANT (TC11)
- 25 DISTRICT ONE TYPICAL PAVEMENT MARKINGS (TC13)
- 26 TRAFFIC CONTROL AND PROTECTION AT TURN BAYS (TO REMAIN OPEN TO TRAFFIC) (TC14)
- 27 PAVEMENT MARKING LETTERS AND SYMBOLS FOR TRAFFIC STAGING (TC16)
- 28 TEMPORARY INFORMATION SIGNING (TC22)
- 29 DETECTOR LOOP INSTALLATION DETAIL FOR ROADWAY RESURFACING (TS07)

THE CONTRACTOR SHALL PATCH BEFORE MILLING

HOT-MIX ASPHALT MIXTURE REQUIREMENTS	
MIXTURE TYPE	AIR VOIDS @ Ndes
HOT-MIX ASPHALT SURFACE COURSE, MIX "D", N70 (IL 9.5mm)	4% @ 70 GYR
POLYMERIZED LEVELING BINDER (MACHINE METHOD), IL 4.75, N50	4% @ 50 GYR
CLASS D PATCHES (HMA BINDER IL 19mm)	4% @ 70 GYR
HOT-MIX ASPHALT REPLACEMENT OVER PATCHES (HMA BINDER IL 19 mm) 3 1/4"	4% @ 70 GYR

THE UNIT WEIGHT USED TO CALCULATE ALL HOT-MIX ASPHALT SURFACE MIXTURE A IS 112 LBS/SQ YD/IN.

THE "AC TYPE" FOR POLYMERIZED HMA MIXES SHALL BE "SBS/SBR PG 70-22" AND FOR NON-POLYMERIZED HMA THE "AC TYPE" SHALE BE "PG 64-22" UNLESS MODIFIED BY DISTRICT ONE SPECIAL PROVISIONS.

FOR "PERCENT OF RAP" SEE DISTRICT ONE SPECIAL PROVISIONS.

FILE NAME =

HIGHWAY STANDARDS

STD. NO. TITLE

442201 - 03 CLASS C AND D PATCHES

604001 - 03 FRAME AND GRATE, TYPE 1

606001 - 04 CONCRETE CURB TYPE B AND COMBINATION CONCRETE CURB AND GUTTER

701606 - OU URBAN LANE CLOSURE, MULTILANE, 2W, WITH MOUNTABLE MEDIAN

701701-99 URBAN LANE CLOSURE, MULTILANE, INTERSECTION

701901 - 01 TRAFFIC CONTROL DEVICES

780001-02 TYPICAL PAVEMENT MARKINGS

781001-93 TYPICAL APPLICATIONS RAISED REFLECTIVE PAVEMENT MARKERS

GENERAL NOTES

- BEFORE STARTING ANY EXCAVATION, THE CONTRACTOR SHALL CALL "J.U.L.I.E."
 AT 800-892-0123 FOR FIELD LOCATIONS OF BURIED ELECTRIC, TELEPHONE AND GAS
 FACILITIES. (48 HOUR NOTIFICATION IS REQUIRED).
- 2. THE CONTRACTOR SHALL COORDINATE CONSTRUCTION ACTIVITIES WITH UTILITY
 COMPANIES
- 3. THE CONTRACTOR WILL NOT BE ALLOWED TO SET UP A YARD OR FIELD OFFICE ON STATE PROPERTY WITHOUT WRITTEN PERMISSION FROM THE DEPARTMENT.
- 4. WHEN ARTIFICIAL LIGHTING IS USED IN NIGHT OPERATIONS THE CONTRACTOR SHALL EXERCISE THE UTMOST PRECAUTIONS IN PREVENTING ADVERSE VISIBILTY TO THE MOTORING PUBLIC AND ADJOINING RESIDENTIAL AREAS.
- 5. WHEN MILLED PAVEMENT IS OPEN TO TRAFFIC THE MAXIMUM GRADE DIFFERENTIAL BETWEEN PASSES OF THE MILLING MACHINE SHALL NOT EXCEED 1 1/2 INCHES (40 MM) WHERE THE SPEED LIMIT IS 45 MPH (80 KM/H) OR LESS AND 1 INCH (25 MM) WHERE THE SPEED LIMIT IS GREATER THAN 45 MPH (80 KM/H). WITH WRITTEN APPROVAL FROM THE ENGINEER, A MAXIMUM GRADE DIFFERENTIAL OF 3 INCHES (75 MM) MAY BE ALLOWED IF THE EDGE OF THE MILLING IS SLOPED A MINIMUM 1:3 (V:H).
- 6. BUTT JOINTS WILL BE INSTALLED AT THE ENDS OF ALL RESURFACING (WHERE RESURFACING MEETS EXISTING PAVEMENT), IN ACCORDANCE WITH THE "BUTT JOINT AND HMA TAPER DETAILS" SHEET INCLUDED IN THE PLANS, UNLESS OTHERWISE SPECIFIED.
- 7. FOR PAVEMENT MARKING AND RAISED REFLECTIVE PAVEMENT MARKERS, REFER TO DISTRICT ONE TYPICAL MARKINGS FOR DETAILS NOT SHOWN.
- THE RESIDENT ENGINEER SHALL CONTACT THE TRAFFIC CONTROL SUPERVISOR AT (847)
 705-4470 A MINIMUM 72 HOURS PRIOR TO THE PLACEMENT OF ANY TEMPORARY TRAFFIC CONTROL DEVICES.
- 9. MATCH EXISTING PAVEMENT MARKINGS AT PROJECT LIMITS.
- THE RESIDENT ENGINEER SHALL CONTACT WALTER CZARNY, AREA TRAFFIC FIELD ENGINEER, AT 847-715-8419 AT LEAST (2) WEEKS PRIOR TO PLACING PERMANENT PAVEMENT MARKINGS.

 USER NAME = .USER_
 DESIGNED - EF
 REVISED - REVISE

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

GREEN BAY ROAD/GLENCOE ROAD - SCOTT AVENUE TO 16TH STREET
INDEX OF SHEETS

SCALE: NTS SHEET NO. OF SHEETS STA. TO STA.

SECTION COUNTY SHEETS NO. COUNTY SHE