

- 7 FINAL PAVEMENT MARKING WITH THERMOPLASTIC PAVEMENT MARKING, LINE 4"
- (8) INSTALL RUMBLE STRIPS ON INNER AND OUTER SHOULDER AS PER DETAIL ON PLAN.
- 9 PLACE AGGREGATE WEDGE SHOULDER, TYPE B.

(10) PLACE RAISED REFLECTIVE PAVEMENT MARKERS AT LANE LINE AND RAMPS.

NOTE:

- * 1. GRADE DIFFERENTIAL BETWEEN LANES SHALL NOT EXCEED 2"
- 2. BARRICADES/DRUMS TO BE PLACED ON THE SHOULDER WITHIN 2' OF THE EDGE OF THE PAVEMENT DURING NON-WORKING HOURS

FILE NAME =	USER NAME = abebawa	DESIGNED -	REVISED -
c:\pw_work\PWIDOT\ABEBAWA\dØ169692\sht-	plan.dgn	DRAWN -	REVISED -
	PLOT SCALE = 50.0000 '/ IN.	CHECKED -	REVISED -
	PLOT DATE = 2/11/2010	DATE -	REVISED -

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

			IL.	ROUTE	55		F.A. I RTE.	SECTION	COUNTY	TOTA SHEET
	SLIGGE	STED	SEC	DIFNCE	ΩF	OPERATIONS	55	99 (1&2) RS-12	WILL	110
JUDGESTED SEGULINOE		OF OF ENATIONS				CONTRACT	NO.			
CALE:		SHEET NO.	1 OF	1 SHEETS	STA.	TO STA.		ILLINOIS FED. A	ID PROJECT	