TRAFFIC SIGNAL LEGEND

E NAME = USER NAME = bouer pw_work\PWIDOT\BAUERDL\d0108315\ts05 dgn		DESIGNED - DAG/BCK DRAWN - BCK CHECKED - DAD	REVISED REVISED REVISED	STATE DEPARTMENT	OF ILLINOIS			DISTRICT ONE STANDARD TRAFFIC SIGNAL DESIGN DETAILS	F.A.P. RTE. 347	SECTION 09-00248-00-RS	COUNTY TOTAL SHEETS COOK 274
VIRELESS ACCESS POINT	R			GROUND CABLE IN CONDUIT NO. 6 SOLID COPPER (GREEN)		(1)	1	CROSSBUCK		> <u></u>	*
WIRELESS DETECTOR SENSOR	R		W	CABLE NO. 14, UNLESS NOTED OTHERWISE, ALL DETECTOR LOOP CABLE TO BE SHIELDED			5	CROSSING GATE		X0 X >	XOX
AN, TILT, ZOOM CAMERA	R [P7Z]1	erzh	PÎZ	RADIO REPEATER DENOTES NUMBER OF CONDUCTORS, ELECTRIC	EKK		RR	FLASHING SIGNAL		$\times \ominus \times$	X ⊖ X
DEO DETECTION ZONE					R ERR	ERR		RAILROAD CANTILEVER MAST ARM		X OX X X	X ex x x
DEO DETECTION CAMERA	R V	(V)	Į ⊙ ∎	RADIO INTERCONNECT	##*O	 +0	## •	RAILROAD CONTROL CABINET		EXISTING	<u>FROFOSED</u>
CROWAVE VEHICLE SENSOR	$\mathbb{R}_{\mathbb{Q}}$	M		PEDESTRIAN SIGNAL HEAD, INTERNATIONAL SYMBOL, WITH COUNTDOWN TIMER		C S	₽ C ★ D			<u>EXISTING</u>	PROPOSED
REFORMED DETECTOR LOOP			Р	12" (300mm) PEDESTRIAN SIGNAL HEAD INTERNATIONAL SYMBOL, SOLID		O	*	RAILROAD SYMBOLS			
ETECTOR LOOP, TYPE I	- <u> </u>			12" (300mm) PEDESTRIAN SIGNAL HEAD INTERNATIONAL SYMBOL, OUTLINED			\$	PREFORMED SAMPLING (SYSTEM) DETECTOR		ÎPSÎ	PS
LUMINATED SIGN NO RIGHT TURN''	R B	©	®	WALK/DON'T WALK SYMBOL		W) W)		(SYSTEM) DETECTOR		PIS PIS	PIS
LUMINATED SIGN 10 LEFT TURN"	R (S)		•	12" (300mm) PEDESTRIAN SIGNAL HEAD		"P"	"P"	PROPOSED INTERSECTION AND SAMPLING (SYSTEM) DETE	CTOR	PP	
CCESSIBLE PEDESTRIAN PUSHBUTTON DETEC	TOR @APS	@APS	APS			♣ 9	4 Y 4 G	PROPOSED INTERSECTION AND SAMPLING (SYSTEM) DETE EXISTING PREFORMED INTERSECTION LOOP DETECTOR	CTOR	[P]	
DESTRIAN PUSHBUTTON DETECTOR	, R	©	•	SIGNAL FACE WITH BACKPLATE. "P" INDICATES PROGRAMMED HEAD			Y	EXISTING INTERSECTION LOOP DETECTOR			
DESTRIAN SIGNAL HEAD	R -	-0	-1			R	R	(SYSTEM) DETECTOR SAMPLING (SYSTEM) DETECTOR			S
ASHER INSTALLATION DENOTES SOLAR POWER)	R O-D-'F''	O-D" ^F "	● → "F"			₹	∢ Y ∢ G	INTERSECTION & SAMPLING		IS	IS
GNAL HEAD OPTICALLY PROGRAMMED	R → "P"	->"p"	— > ′′P′′	SIGNAL FACE			G 4,0 3	SIGNAL POST AND FOUNDATION TO BE REMOVED	RMF O		
GMAL HEAD CONSTRUCTION STAGES JMBERS INDICATE THE CONSTRUCTION STAG GNAL HEAD WITH BACKPLATE	EE) +\□ R	+-	2 + >	TELLOW AND GREEN TRAFFIC SIGNAL FACE		Ö R	R	STEEL COMBINATION MAST ARM ASSEMBLY AND POLE WITH LUMINAIRE AND FOUNDATION TO BE REMOVED	RMF O-X		
GNAL HEAD GNAL HEAD CONSTRUCTION STAGES	$\overset{\vdash}{\sim}$		2	12" (300mm) RED WITH 8" (200mm) YELLOW AND GREEN TRAFFIC SIGNAL FACE		R		FOUNDATION TO BE REMOVED	0		
Y WIRE	, R	>	>	12" (300mm) TRAFFIC SIGNAL SECTION		R	R	ALUMINUM MAST ARM POLE AND	RMF		
MPORARY WOOD POLE (CLASS 5 OR TTER) 45 FOOT (13.7m) MINIMUM	^R ⊗	\otimes	•	RELOCATE ITEM ABANDON ITEM	KL A			STEEL MAST ARM POLE AND FOUNDATION TO BE REMOVED	RMF O		
GNAL POST	RO	0 .	•	REMOVE ITEM	R			CONTROLLER CABINET AND FOUNDATION TO BE REMOVED	RCF		
TEEL COMBINATION MAST ARM SSEMBLY AND POLE WITH PTZ CAMERA	R PTZ[1]	Q	PTZ¶	SYSTEM ITEM INTERSECTION ITEM		S	S in a	(H) HANDHOLE, (P) POST, (M) MAST ARM, OR (S) SERVICE		C 11 -	^C III—
TEEL COMBINATION MAST ARM SSEMBLY AND POLE WITH LUMINAIRE	RO-X-	O-X	• ×	COILABLE NONMETALLIC CONDUIT (EMPTY)			CNC	NOTED ON PLANS) GROUND ROD AT (C) CONTROLLER,		~	<u> </u>
UMINUM MAST ARM ASSEMBLY AND POLE	R	0		COMMON TRENCH			ст	FIBER OPTIC CABLE NO. 62.5/125, (NUMBER OF FIBERS & TYPE TO BE		- ←	
) POLE OR (G) GROUND MOUNT TEEL MAST ARM ASSEMBLY AND POLE	R_	P _T	Ī	TEMPORARY SPAN WIRE, TETHER WIRE, AND CABLE	R			FIBER OPTIC CABLE NO. 62.5/125, MM12F SM12F		 24F	
) POLE OR (G) GROUND MOUNT ELEPHONE CONNECTION	-,□_R :		- -	GALVANIZED STEEL CONDUIT IN TRENCH (T) OR PUSHED (P)	Saladi.			FIBER OPTIC CABLE NO. 62.5/125, MM12F		—(12F)—	
NINTERRUPTIBLE POWER SUPPLY ERVICE INSTALLATION,	UPS	EUPS	UPS	DOUBLE HANDHOLE JUNCTION BOX	R R			NO. 18 3 PAIR TWISTED, SHIELDED		- 6-	6—
ASTER MASTER CONTROLLER	R	EMMC	MMC	HEAVY DUTY HANDHOLE	R R	H	H	VENDOR CABLE FOR CAMERA COPPER INTERCONNECT CABLE,			(V)
ASTER CONTROLLER	* ***	[EMC]	MC	HANDHOLE				VENDOR CARLE FOR CAMERA		α	
DMMUNICATIONS CABINET	C C	E C C	СС		R	-		COAXIAL CABLE		— <u>©</u> —	—©—
AILROAD CONTROL CABINET	⊠ ^R			EMERGENCY VEHICLE LIGHT DETECTOR CONFIRMATION BEACON	R _{0−} Q	o-⊲	— ~ ·	NO. 14 1/C, UNLESS NOTED OTHERWISE)	· ·
ONTROLLER CABINET	R			EMEDICANON VEHICLE LIGHT DETECTOR	R	\ll	•	ELECTRIC CABLE IN CONDUIT, TRACER,	¥ .		(1)