TRAFFIC SIGNAL LEGEND										
ITEM	REMOVAL	EXISTING	PROPOSED	ITEM	REMOVAL	EXISTING	PROPOSED	ITEM	REMOVAL EXISTING	PROPOSED
CONTROLLER CABINET	\bowtie^R	\bowtie		EMERGENCY VEHICLE LIGHT DETECTOR	R ≪	≪	~	ELECTRIC CABLE IN CONDUIT, TRACER, NO. 14 1/C, UNLESS NOTED OTHERWISE	— <u>Ú</u> —	
RAILROAD CONTROL CABINET	Minorage and Minor		⊳ ∢	CONFIRMATION BEACON	R_{O-0}	0–0	•-(NO. 14 17C, UNLESS NOTED OTHERWISE	,-	_
COMMUNICATIONS CABINET	CC R	ECC	СС		R ⊠	_		COAXIAL CABLE	_ ©—	— <u>c</u>
MASTER CONTROLLER	[00]	EMC	MC	HANDHOLE					,	
MASTER MASTER CONTROLLER		EMMC	MMC	HEAVY DUTY HANDHOLE	R	H		VENDOR CABLE FOR CAMERA	—	
UNINTERRUPTIBLE POWER SUPPLY	R UPS	EUPS	UPS	DOUBLE HANDHOLE	R			COPPER INTERCONNECT CABLE, NO. 18 3 PAIR TWISTED, SHIELDED	-6)-	6)
SERVICE INSTALLATION, (P) POLE OR (G) GROUND MOUNT	-D- ^R	- <u>-</u> -	- 	JUNCTION BOX GALVANIZED STEEL CONDUIT	R 🔘	@	•	FIBER OPTIC CABLE NO. 62.5/125, MM12F	-(2 1)	Ŭ
TELEPHONE CONNECTION (P) POLE OR (G) GROUND MOUNT	R	P	P	IN TRENCH (T) OR PUSHED (P)				FIBER OPTIC CABLE	-245	(24F)
STEEL MAST ARM ASSEMBLY AND POLE	R	0	•	TEMPORARY SPAN WIRE, TETHER WIRE, AND CABLE	R			NO. 62,5/125, MM12F SM12F		
ALUMINUM MAST ARM ASSEMBLY AND POLE	R	0		COMMON TRENCH			ст	FIBER OPTIC CABLE NO. 62.5/125, (NUMBER OF FIBERS & TYPE TO BE	_<	
STEEL COMBINATION MAST ARM	D			COILABLE NONMETALLIC CONDUIT (EMPTY)			CNC	NOTED ON PLANS)	\triangleright	
ASSEMBLY AND POLE WITH LUMINAIRE	"ò-≭——	O-X	• *	SYSTEM ITEM		S	S	GROUND ROD AT (C) CONTROLLER,	C	C
STEEL COMBINATION MAST ARM ASSEMBLY AND POLE WITH PTZ CAMERA	RO	Q	PIZI	INTERSECTION ITEM		I	IP	(H) HANDHOLE, (P) POST, (M) MAST ARM, OR (S) SERVICE	- ∥•	₩-•
SIGNAL POST	R _O	0	•	REMOVE ITEM	R			CONTROLLER CABINET AND FOUNDATION TO BE REMOVED	RCF	
TEMPORARY WOOD POLE (CLASS 5 OR	O R⊗	⊗	∞	RELOCATE ITEM	RL			FUUNDATION TO BE REMOVED		
BETTER) 45 FOOT (13.7m) MINIMUM		-	•	ABANDON ITEM	Α			STEEL MAST ARM POLE AND FOUNDATION TO BE REMOVED	ORMF.	
GUY WIRE	<u>>R</u>	>	>_	12" (300mm) TRAFFIC SIGNAL SECTION		R	R	ALUMINUM MAST ARM POLE AND	RMF	
SIGNAL HEAD	-R →	\rightarrow	-	12" (300mm) RED WITH 8" (200mm)		R		FOUNDATION TO BE REMOVED		
SIGNAL HEAD CONSTRUCTION STAGES (NUMBERS INDICATE THE CONSTRUCTION STAGE)	R		2	YELLOW AND GREEN TRAFFIC SIGNAL FACE		R Y C R	R	STEEL COMBINATION MAST ARM ASSEMBLY AND POLE WITH LUMINAIRE AND FOUNDATION TO BE REMOVED	RMF O -X	
SIGNAL HEAD WITH BACKPLATE	+t> ^R	+1>	+				Υ	SIGNAL POST AND FOUNDATION	DHE	
SIGNAL HEAD OPTICALLY PROGRAMMED	-\bar{\bar{\bar{\bar{\bar{\bar{\bar{	— > ′′p′′	— > "P"	SIGNAL FACE			G 4 Y	TO BE REMOVED	RMF	
FLASHER INSTALLATION (S DENOTES SOLAR POWER)	R O- ⊳ ′′F′′	O+D″F″	●→ "F"				 G	INTERSECTION & SAMPLING (SYSTEM) DETECTOR	[IS]	IS
PEDESTRIAN SIGNAL HEAD	R -	-0	-1			R	R	SAMPLING (SYSTEM) DETECTOR	[s]	S
PEDESTRIAN PUSHBUTTON DETECTOR	R	·	(a)	SIGNAL FACE WITH BACKPLATE. "P" INDICATES PROGRAMMED HEAD		Ğ	G	EXISTING INTERSECTION LOOP DETECTOR		
ACCESSIBLE PEDESTRIAN PUSHBUTTON DETECTOR	R APS	@APS	APS			(*P')	← C	PROPOSED INTERSECTION AND SAMPLING (SYSTEM) DETECT EXISTING PREFORMED INTERSECTION LOOP DETECTOR		
ILLUMINATED SIGN "NO LEFT TURN"	R	•	•				"P"	PROPOSED INTERSECTION AND SAMPLING (SYSTEM) DETECT	OR PP	
			<u> </u>	12" (300mm) PEDESTRIAN SIGNAL HEAD WALK/DON'T WALK SYMBOL		(W)		PREFORMED INTERSECTION AND SAMPLING (SYSTEM) DETECTOR	PIS	PIS
ILLUMINATED SIGN "NO RIGHT TURN"	R		®	12" (300mm) PEDESTRIAN SIGNAL HEAD				PREFORMED SAMPLING (SYSTEM) DETECTOR	PS	PS
DETECTOR LOOP, TYPE I		[7		INTERNATIONAL SYMBOL, OUTLINED				, N.E. 61/11/E 67/11/12/11/11	¥-1	1.01
PREFORMED DETECTOR LOOP		F	Р	12" (300mm) PEDESTRIAN SIGNAL HEAD INTERNATIONAL SYMBOL, SOLID		()	*	RAILROAD	SYMBOLS	
MICROWAVE VEHICLE SENSOR	R (M)1	(M)	M	PEDESTRIAN SIGNAL HEAD, INTERNATIONAL SYMBOL, WITH COUNTDOWN TIMER		C C	C AD		EXISTING	PROPOSED
VIDEO DETECTION CAMERA	R [√]1	[Vp	V	RADIO INTERCONNECT	## * O	- 111-0		RAILROAD CONTROL CABINET		
VIDEO DETECTION ZONE					1.	,		RAILROAD CANTILEVER MAST ARM	XOX X X	X ox x
	R			RADIO REPEATER	R ERR	ERR	RR	FLASHING SIGNAL	∑⊖ ∑	X O X
PAN, TILT, ZOOM CAMERA				DENOTES NUMBER OF CONDUCTORS, ELECTRIC CABLE NO. 14, UNLESS NOTED OTHERWISE,		_5		CROSSING GATE	X0X>	XOX-
WIRELESS DETECTOR SENSOR	RW	(W)	W	ALL DETECTOR LOOP CABLE TO BE SHIELDED				CROSSBUCK	202	*
WIRELESS ACCESS POINT	R →			GROUND CABLE IN CONDUIT NO. 6 SOLID COPPER (GREEN)		(1)	(1)	CHOSSBUCK	△	
LE NAME = 06231-SGNL-DTLS-01 - P06 USER NAME = bauerdl		ESIGNED DAG/BCK HECKED BCK	REVISED REVISED	STATE	OF ILLINO	s		DISTRICT ONE	F.A.U. SECTION RTE. SECTION 1600 06-00008-00-BT	COUNTY TOTA SHEE
PLOT SCALE = 50.0000 '		RAWN — DAD HECKED — 10-28-09		DEPARTMENT (SCALE: NON	STANDARD TRAFFIC SIGNAL DESIGN DETAILS E SHEET NO. 6 OF 6 SHEETS STA. TO STA.	1600 06-0008-00-B1	WILL 73 CONTRACT NO. 60