

GIRDER 1

Location	Station	Offset	Theoretical Grade Elevation	Elevation Adjusted for Dead Load Deflection
Bk. S. Abut.	8019+35.07	-19.29	621.54	621.54
⊕ Brg. S. Abut.	8019+38.66	-19.29	621.62	621.62
AA	8019+48.66	-19.29	621.82	621.89
AB	8019+58.66	-19.29	622.02	622.15
AC	8019+68.66	-19.29	622.20	622.39
AD	8019+78.66	-19.29	622.38	622.61
AE	8019+88.66	-19.29	622.55	622.81
AF	8019+98.66	-19.29	622.71	622.99
AG	8020+08.66	-19.29	622.86	623.14
AH	8020+18.66	-19.29	623.00	623.26
AJ	8020+28.66	-19.29	623.13	623.37
AK	8020+38.66	-19.29	623.25	623.46
AL	8020+48.66	-19.29	623.36	623.53
AM	8020+58.66	-19.29	623.46	623.58
AN	8020+68.66	-19.29	623.55	623.64
AP	8020+78.66	-19.29	623.63	623.68
AR	8020+88.66	-19.29	623.71	623.73
⊕ Brg. Pier	8021+02.66	-19.29	623.79	623.79
AS	8021+12.66	-19.29	623.84	623.85
AT	8021+22.66	-19.29	623.89	623.91
AU	8021+32.66	-19.29	623.92	623.97
AV	8021+42.66	-19.29	623.94	624.03
AW	8021+52.66	-19.29	623.95	624.08
AX	8021+62.66	-19.29	623.96	624.12
AY	8021+72.66	-19.29	623.95	624.15
AZ	8021+82.66	-19.29	623.93	624.16
BA	8021+92.66	-19.29	623.91	624.16
BB	8022+02.66	-19.29	623.87	624.13
BC	8022+12.66	-19.29	623.83	624.08
BD	8022+22.66	-19.29	623.78	624.00
BE	8022+32.66	-19.29	623.71	623.90
BF	8022+42.66	-19.29	623.64	623.78
BG	8022+52.66	-19.29	623.56	623.65
⊕ Brg. N. Abut.	8022+66.66	-19.29	623.43	623.43
Bk. N. Abut.	8022+70.25	-19.29	623.39	623.39

GIRDER 2

Location	Station	Offset	Theoretical Grade Elevation	Elevation Adjusted for Dead Load Deflection
Bk. S. Abut.	8019+36.86	-14.38	621.48	621.48
⊕ Brg. S. Abut.	8019+40.45	-14.38	621.56	621.56
AA	8019+50.45	-14.38	621.76	621.83
AB	8019+60.45	-14.38	621.95	622.08
AC	8019+70.45	-14.38	622.14	622.32
AD	8019+80.45	-14.38	622.31	622.54
AE	8019+90.45	-14.38	622.48	622.74
AF	8020+00.45	-14.38	622.64	622.91
AG	8020+10.45	-14.38	622.78	623.06
AH	8020+20.45	-14.38	622.92	623.19
AJ	8020+30.45	-14.38	623.05	623.29
AK	8020+40.45	-14.38	623.17	623.38
AL	8020+50.45	-14.38	623.28	623.45
AM	8020+60.45	-14.38	623.38	623.50
AN	8020+70.45	-14.38	623.47	623.55
AP	8020+80.45	-14.38	623.55	623.60
AR	8020+90.45	-14.38	623.62	623.64
⊕ Brg. Pier	8021+04.45	-14.38	623.70	623.70
AS	8021+14.45	-14.38	623.75	623.76
AT	8021+24.45	-14.38	623.79	623.82
AU	8021+34.45	-14.38	623.82	623.87
AV	8021+44.45	-14.38	623.84	623.93
AW	8021+54.45	-14.38	623.85	623.97
AX	8021+64.45	-14.38	623.86	624.01
AY	8021+74.45	-14.38	623.85	624.04
AZ	8021+84.45	-14.38	623.83	624.05
BA	8021+94.45	-14.38	623.80	624.04
BB	8022+04.45	-14.38	623.77	624.01
BC	8022+14.45	-14.38	623.72	623.95
BD	8022+24.45	-14.38	623.67	623.88
BE	8022+34.45	-14.38	623.60	623.78
BF	8022+44.45	-14.38	623.53	623.66
BG	8022+54.45	-14.38	623.45	623.53
⊕ Brg. N. Abut.	8022+68.45	-14.38	623.31	623.31
Bk. N. Abut.	8022+72.04	-14.38	623.28	623.28

GIRDER 3

Location	Station	Offset	Theoretical Grade Elevation	Elevation Adjusted for Dead Load Deflection
Bk. S. Abut.	8019+38.65	-9.46	621.42	621.42
⊕ Brg. S. Abut.	8019+42.24	-9.46	621.49	621.49
AA	8019+52.24	-9.46	621.70	621.76
AB	8019+62.24	-9.46	621.89	622.02
AC	8019+72.24	-9.46	622.07	622.26
AD	8019+82.24	-9.46	622.25	622.47
AE	8019+92.24	-9.46	622.41	622.67
AF	8020+02.24	-9.46	622.57	622.84
AG	8020+12.24	-9.46	622.71	622.99
AH	8020+22.24	-9.46	622.85	623.11
AJ	8020+32.24	-9.46	622.97	623.22
AK	8020+42.24	-9.46	623.09	623.30
AL	8020+52.24	-9.46	623.20	623.37
AM	8020+62.24	-9.46	623.30	623.42
AN	8020+72.24	-9.46	623.38	623.47
AP	8020+82.24	-9.46	623.46	623.51
AR	8020+92.24	-9.46	623.53	623.55
⊕ Brg. Pier	8021+06.24	-9.46	623.62	623.62
AS	8021+16.24	-9.46	623.66	623.67
AT	8021+26.24	-9.46	623.70	623.72
AU	8021+36.24	-9.46	623.73	623.78
AV	8021+46.24	-9.46	623.75	623.83
AW	8021+56.24	-9.46	623.76	623.88
AX	8021+66.24	-9.46	623.76	623.91
AY	8021+76.24	-9.46	623.75	623.94
AZ	8021+86.24	-9.46	623.73	623.94
BA	8021+96.24	-9.46	623.70	623.93
BB	8022+06.24	-9.46	623.66	623.90
BC	8022+16.24	-9.46	623.62	623.85
BD	8022+26.24	-9.46	623.56	623.77
BE	8022+36.24	-9.46	623.49	623.67
BF	8022+46.24	-9.46	623.42	623.55
BG	8022+56.24	-9.46	623.33	623.41
⊕ Brg. N. Abut.	8022+70.24	-9.46	623.20	623.20
Bk. N. Abut.	8022+73.83	-9.46	623.16	623.16

GIRDER 4

Location	Station	Offset	Theoretical Grade Elevation	Elevation Adjusted for Dead Load Deflection
Bk. S. Abut.	8019+40.44	-4.54	621.36	621.36
⊕ Brg. S. Abut.	8019+44.03	-4.54	621.43	621.43
AA	8019+54.03	-4.54	621.63	621.70
AB	8019+64.03	-4.54	621.82	621.95
AC	8019+74.03	-4.54	622.01	622.19
AD	8019+84.03	-4.54	622.18	622.41
AE	8019+94.03	-4.54	622.34	622.60
AF	8020+04.03	-4.54	622.49	622.77
AG	8020+14.03	-4.54	622.64	622.92
AH	8020+24.03	-4.54	622.77	623.04
AJ	8020+34.03	-4.54	622.90	623.14
AK	8020+44.03	-4.54	623.01	623.22
AL	8020+54.03	-4.54	623.12	623.29
AM	8020+64.03	-4.54	623.21	623.34
AN	8020+74.03	-4.54	623.30	623.39
AP	8020+84.03	-4.54	623.38	623.43
AR	8020+94.03	-4.54	623.45	623.47
⊕ Brg. Pier	8021+08.03	-4.54	623.53	623.53
AS	8021+18.03	-4.54	623.57	623.58
AT	8021+28.03	-4.54	623.61	623.63
AU	8021+38.03	-4.54	623.63	623.69
AV	8021+48.03	-4.54	623.65	623.74
AW	8021+58.03	-4.54	623.66	623.78
AX	8021+68.03	-4.54	623.66	623.81
AY	8021+78.03	-4.54	623.65	623.84
AZ	8021+88.03	-4.54	623.63	623.84
BA	8021+98.03	-4.54	623.60	623.83
BB	8022+08.03	-4.54	623.56	623.79
BC	8022+18.03	-4.54	623.51	623.74
BD	8022+28.03	-4.54	623.45	623.66
BE	8022+38.03	-4.54	623.38	623.56
BF	8022+48.03	-4.54	623.30	623.44
BG	8022+58.03	-4.54	623.22	623.30
⊕ Brg. N. Abut.	8022+72.03	-4.54	623.08	623.08
Bk. N. Abut.	8022+75.62	-4.54	623.04	623.04

PROFILE GRADE LINE

Location	Station	Offset	Theoretical Grade Elevation	Elevation Adjusted for Dead Load Deflection
Bk. S. Abut.	8019+42.09	0.00	621.30	621.30
⊕ Brg. S. Abut.	8019+45.68	0.00	621.38	621.38
AA	8019+55.68	0.00	621.57	621.64
AB	8019+65.68	0.00	621.76	621.89
AC	8019+75.68	0.00	621.94	622.13
AD	8019+85.68	0.00	622.11	622.34
AE	8019+95.68	0.00	622.28	622.53
AF	8020+05.68	0.00	622.43	622.70
AG	8020+15.68	0.00	622.57	622.85
AH	8020+25.68	0.00	622.70	622.97
AJ	8020+35.68	0.00	622.83	623.07
AK	8020+45.68	0.00	622.94	623.15
AL	8020+55.68	0.00	623.04	623.21
AM	8020+65.68	0.00	623.14	623.27
AN	8020+75.68	0.00	623.22	623.31
AP	8020+85.68	0.00	623.30	623.35
AR	8020+95.68	0.00	623.37	623.39
⊕ Brg. Pier	8021+09.68	0.00	623.44	623.44
AS	8021+19.68	0.00	623.49	623.49
AT	8021+29.68	0.00	623.52	623.55
AU	8021+39.68	0.00	623.55	623.60
AV	8021+49.68	0.00	623.56	623.65
AW	8021+59.68	0.00	623.57	623.69
AX	8021+69.68	0.00	623.57	623.72
AY	8021+79.68	0.00	623.55	623.74
AZ	8021+89.68	0.00	623.53	623.75
BA	8021+99.68	0.00	623.50	623.73
BB	8022+09.68	0.00	623.46	623.70
BC	8022+19.68	0.00	623.41	623.64
BD	8022+29.68	0.00	623.35	623.56
BE	8022+39.68	0.00	623.28	623.46
BF	8022+49.68	0.00	623.20	623.33
BG	8022+59.68	0.00	623.11	623.19
⊕ Brg. N. Abut.	8022+73.68	0.00	622.97	622.97
Bk. N. Abut.	8022+77.27	0.00	622.93	622.93

GIRDER 5

Location	Station	Offset	Theoretical Grade Elevation	Elevation Adjusted for Dead Load Deflection
Bk. S. Abut.	8019+42.23	0.38	621.30	621.30
⊕ Brg. S. Abut.	8019+45.82	0.38	621.37	621.37
AA	8019+55.82	0.38	621.57	621.64
AB	8019+65.82	0.38	621.76	621.89
AC	8019+75.82	0.38	621.94	622.12
AD	8019+85.82	0.38	622.11	622.34
AE	8019+95.82	0.38	622.27	622.53
AF	8020+05.82	0.38	622.42	622.70
AG	8020+15.82	0.38	622.56	622.84
AH	8020+25.82	0.38	622.70	622.96
AJ	8020+35.82	0.38	622.82	623.06
AK	8020+45.82	0.38	622.93	623.14
AL	8020+55.82	0.38	623.04	623.21
AM	8020+65.82	0.38	623.13	623.26
AN	8020+75.82	0.38	623.22	623.30
AP	8020+85.82	0.38	623.29	623.34
AR	8020+95.82	0.38	623.36	623.38
⊕ Brg. Pier	8021+09.82			