


SECTION THRU SIDEWALK & WINGWALL



TWO SIDEWALK
ON APPROACH PAV'TS
BILL OF MATERIALS

Bar	No.	Size	Length	Shape
b11(E)	32	#5	29'-8''	
c11(E)	124 124	#5 #5	2'-5'' 7'-2''	
Reinforcement Bars Epoxy Coated			Pound	2,240
Concrete Superstructure			Cu. Yd.	30.0

QUANTITIES ARE SHOWN FOR INFORMATION ONLY. COST IS INCLUDED WITH BRIDGE APPROACH PAVEMENT (SPECIAL).

PLAN - SIDEWALK & WINGWALL

(North - West as shown, other corners similar)

NOTES:

Work this Sheet with Sheets 1 & 2 of "Bridge Approach Pavement (Special)" Sheets.

Reinforcement Bars designated (E) shall be epoxy coated.

Sealant shall be non-staining gray one component non-sag elastomeric gun grade polyurethane meeting the requirements of ASTM C-920, Type S, Grade NS, Class 25, Use T.

REVISIONS
NAME DATE

ILLINOIS DEPARTMENT OF TRANSPORTATION

F.A.I. 94 (DAN RYAN EXPRESSWAY)

BRIDGE APPROACH PAVEMENT

(SPECIAL)

SCALE: NONE DRAWN BY:
DATE: MARCH 25, 2005 CHECKED BY: