

F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
612	1109.110RS-1		40	2
STA.		TO STA.		
FED. ROAD DIST. NO.		ILLINOIS	FED. AID PROJECT	

*FULTON & SCHUYLER

COMMITMENTS

Commitments are not to be altered without the written approval of all parties to which the commitment was made.

There are no commitments on this project.

EXCEPTIONS TO DESIGN POLICY

There are no exceptions to design policy on this project.

GENERAL NOTES

PROPERTY OWNER ACCESS REQUIREMENT

Access must be maintained to all existing properties during construction per Article 107.09 unless arrangements are made in writing by the Contractor with the property owners with a copy to the Engineer for short-term closures.

AGGREGATE SHOULDERS, TYPE B

Aggregate Shoulders, Type B shall be required for all granular construction of side roads, entrances, and mailbox turnouts, whether or not portions of the surfaces thus constructed are to be covered with a bituminous surface, except where noted differently on the plans.

GENERAL NOTES

BITUMINOUS CONCRETE MIXTURE REQUIREMENTS

Location :	Surface
Mixture Use(s):	Bituminous Pavement Mainline
RAP % (Max)**:	15%
AC/PG:	64-22
Design Air Voids:	4.2% @ N=50
Mixture Composition: (Gradation Mixture)	IL 9.5 or IL 12.5
Friction Aggregate	Mixture D (dolomite only)

**If the RAP option is selected, the asphalt cement grade may need to be adjusted; this will be determined by the Engineer.

PAVING SURFACE COURSE, CONTINUOUS

Continuous paving operations on the main roadway shall be maintained at all times during the construction of the bituminous surface. No interruptions for side roads, entrances, turn lanes, etc. will be allowed.

REVISIONS	
NAME	DATE

ILLINOIS DEPARTMENT OF TRANSPORTATION
**COMMITMENTS,
 EXCEPTIONS TO DESIGN
 POLICY, GENERAL NOTES**

SCALE: VERT. _____
 HORIZ. _____
 DATE _____ DRAWN BY _____
 CHECKED BY _____

PLOT DATE = 3/18/2005
 FILE NAME = c:\projects\68333\68333.dgn
 PLOT SCALE = 1/8"=1'-0"
 REFERENCE = 4819