



NOTE: WARP BASIN TO CONFORM TO NATURAL STREAM CHANNEL. TOP OF RIPRAP IN FLOOR OF BASIN SHOULD BE AT THE SAME ELEVATION OR LOWER THAN NATURAL CHANNEL BOTTOM AT SECTION A-A.

RIPRAP STILLING BASIN SCHEDULE													
STATION	OFFSET	BARREL WIDTH OF BOX CULVERT	BOX CULVERT OUTLET FLOWLINE	DISSIPATOR POOL LENGTH	APRON LENGTH	OVERALL BASIN LENGTH	DEPTH OF BASIN BELOW THE CULVERT FLOWLINE	THICKNESS OF APPROACH	TYPICAL THICKNESS OF BASIN	STONE RIPRAP CLASS A4	FILTER FABRIC FOR USE WITH RIPRAP	EARTH EXCAVATION FOR EROSION CONTROL	GABIONS
		W_b	C_{FL}	L_p	L_a	L_b	h_s	T_a	T_b	(SQ YD)	(SQ YD)	(CU YD)	(CU YD)
		(FT)	(FT)	(FT)	(FT)	(FT)	(FT)	(FT)	(FT)				
951+33.21	LT	4.0	599.87	12.0	4.0	16	0.90	1.5	1.0	27	27	12	12
1034+79.00	RT	4.0	551.40	37.5	18.5	56	3.75	3.0	2.0	248	248	344	344
TOTALS										275	275	356	356

REVISIONS		ILLINOIS DEPARTMENT OF TRANSPORTATION RIPRAP STILLING BASIN SCHEDULE AND DETAILS DRAWN BY MLO CHECKED BY TGC DATE 8/02
NAME	DATE	