



HEXAGON NUT
 AMER. NAT'L. STD. HEAVY HEX. FLAT NUT
 (ANSI B 18.2.2 - 1972)

FLAT WASHER
 AMER. NAT'L. STD. TYPE "B" SERIES "W"
 (ANSI B 18.22.1-1945, R1975)

LOCK WASHER
 AMER. NAT'L. STD. HELICAL SPRING LOCK WASHER, REGULAR
 (ANSI B 18.21.1 - 1972)

MATERIAL:

ASTM A-36 MODIFIED STEEL, 55 000 LBS. MINIMUM YIELD.
HARDWARE TO BE FURNISHED & ATTACHED IN PLACE ON ROD FOR SHIPPING:
 2 HEX. NUTS, HEAVY, GALV., 1"
 2 WASHERS, STEEL, ROUND, GALV., TYPE "B", SERIES "W", 1"
 1 WASHER, LOCK, STEEL, GALV., HELICAL SPRING, REGULAR, 1"
 BOLT & NUTS SHALL HAVE AN AMERICAN STANDARD CLASS 2 OR 3 FIT.
 (NUT IS TAPPED OVERSIZE BY 1/32")

1" x 60"
STEEL ANCHOR BOLT
 CONMODITY CODE 37-8180-0220

REVISED	CITY OF CHICAGO DEPT. OF STREETS AND SANITATION BUREAU OF ELECTRICAL ENGINEERING	
A 9-4-1983	DRAWN EUGENE GERULIS	CHECKED A. WALLACE
B	DESIGN ENGINEER	DATE M. SHINE
C	ENGINEER IN CHARGE	
D	SUPERVISOR	
E	DEPUTY SUPERVISOR	
F	DEPUTY SUPERVISOR	
G	SIZE 17" x 26"	SCALE 1/8" = 1'-0"

830
 DATE: SEP. 9, 1983

A ZINC COATING, 0.0021 INCH IN THICKNESS SHALL BE APPLIED OVER THIS LENGTH AND COVERED WITH HEAVY HO-BX-10, OR EQUAL, RUST INHIBITING COMPOUND

REVISIONS	
NAME	DATE

02/02/2005 09:02:37 AM