

TRAFFIC CONTROL GENERAL NOTES

PUBLIC INFORMATION

SIGN

W21-I116-6048

(19)

TEMPORARY PAVEMENT MARKINGS SHALL BE PLACED TO PROVIDE 12' WIDE TEMPORARY DRIVING LANES WHERE PRACTICABLE. MINIMUM TEMPORARY DRIVING LANE WIDTH IS 11'.

DOTTED PAVEMENT MARKINGS SHALL CONSIST OF 4' SKIP AND 2' DASH.


TEMPORARY PAVEMENT MARKINGS ARE NOT REQUIRED ON ACCESS ROADS EXCEPT AS NOTED ON THE PLANS. PERMANENT PAVEMENT MARKINGS SHALL BE APPLIED TO THE ACCESS ROADS AS SOON AS PRACTICABLE.

PUBLIC INFORMATION SIGN (19) SHALL CONSIST OF "PLEASE SLOW DOWN, MY MOMMY/DADDY WORKS HERE."

STAGES 1-3: TEMPORARY PAVEMENT MARKING
LINE 4" (WHITE EDGE LINES) SHALL BE PROVIDED
ALONG ALL OUTSIDE EDGES OF MAINLINE DRIVING
LANES. IN LOCATIONS WHERE MAINLINE DRIVING
LANES ARE SEPARATED BY A MEDIAN (RAISED OR
DEPRESSED), TEMPORARY PAVEMENT MARKING
LINE 4" (YELLOW EDGE LINES) SHALL ALSO BE
PROVIDED ALONG THE INSIDE (MEDIAN) EDGE OF
DRIVING LANE.

STAGE 2: ALL ACCESS ROAD PERMANENT SIGNAGE AS DELINEATED ON SHEETS 175 TO 180 SHALL BE INSTALLED PRIOR TO OPENING ACCESS ROADS TO TRAFFIC.

STAGE 4: TRAFFIC CONTROL AND PROTECTION, STANDARD 70142: SHALL BE USED DURING PLACEMENT OF THE FINAL LIFT OF BITUMINOUS SURFACE COURSE. SHORT-TERM PAVEMENT MARKINGS HAVE BEEN CALCULATED FOR TWO ITERATIONS OF APPLICATION. TWO ITERATIONS MAY NOT BE REQUIRED AT ALL LOCATIONS. APPLICATION OF SHORT-TERM PAVEMENT MARKINGS WILL DEPEND ON CONTRACTOR'S METHOD OF PAVING FINAL SURFACE COURSE.



TRAFFIC CONTROL
GENERAL NOTES AND SIGNS

F.A.P. 103 (IL. RTE. 13/15) SECTION 27-1R - ST. CLAIR CO.

SCALE: DRAWN BY CRO
DATE Febuary 11, 2005 CHECKED BY RCY